



NOTE:
 IN THE "CROSS-OVER AREA" OF REINFORCEMENT, ONE OF THE LAYERS OF REINFORCEMENT SHOULD BE LOWERED OR RAISED ONE COURSE TO ALLOW PLACEMENT OF THE REINFORCEMENT WITH THE PRINCIPLE REINFORCEMENT STRENGTH DIRECTION PROPERLY ORIENTATED. THE REINFORCEMENT SHOULD NOT EXTEND INTO THE SEGMENTAL RETAINING WALL UNITS ON THE RETURN LEG OF THE 90-DEGREE CORNER.

ANCHOR DIAMOND PRO™
X 90-DEGREE OUTSIDE CORNER W/ GRID
WX (NOT TO SCALE)



RETAINING WALL SYSTEMS
Preferred Worldwide For Selection and Quality

These graphical representations are intended for preliminary design purposes only, and are not to be used for construction without the signature of a registered professional engineer.

All information herein © 2005 Anchor Wall Systems

Drawn By:

AWS

Date:

4/26/2005

Scale:

NTS

Drawing Title:

ANCHOR DIAMOND PRO
OUTSIDE CORNER DETAILS 2

Project Information:

ANCHOR RETAINING WALL SYSTEMS
 TYPICAL WALL DETAILS